



WIRELESS TRANSDUCER TRANSMITTER

TYPICAL APPLICATIONS

For use where having a wireless connection between the transducer and the control panel or telemetry panel is required.

DESCRIPTION

**MADE IN
THE U.S.A.**

TRANSMITTER

The Wireless Transducer Transmitter performs the liquid level measurement and sends the data by radio signal to the Receiver. The device consists of two parts, connected by a cable; the Transmitter and the Pressure Sensor. The Transmitter is suspended above the liquid, and the Pressure Sensor is submerged in the liquid near the bottom of the tank.

The Transmitter transmits updated level data and battery condition data once every second. To conserve battery power, most of the circuitry is powered down and asleep between updates. After being asleep for one second, the Transmitter wakes up, powers up the Pressure Sensor, checks the level, checks the condition of the battery, transmits the new data to the Receiver, and then goes back to sleep.

PRESSURE SENSOR

When submerged in liquid, the Pressure Sensor converts the pressure exerted by the liquid into an analog voltage signal that represents the liquid level. The sensor measures the absolute pressure, so a correction for the barometric pressure must be made. This correction is performed in the Receiver where the local barometric pressure is measured and subtracted from the signal.

A stainless steel diaphragm and silicone oil fill is provided to isolate and protect the pressure sensor from the liquid being measured.

The weight of the Pressure Sensor acts to reduce its movement when placed in a moving liquid. A Strength Cord in the cable provides ample support for its weight. A Kellems Grip is provided to secure the Pressure Sensor Cable to a float hanger.

The Pressure Sensor and the Transmitter come connected together tested and calibrated as a unit. It is calibrated to read levels between 0.0 feet and 34.6 feet and provide a 16 bit number to the Receiver that represents the measured level.



TRANSMITTER SPECIFICATIONS

Enclosure Material:	PVC
Operating Temp:	-20 to +65 °C
Radio Frequency:	2.4 GHz
Battery:	Lithium, 3.6V, Size "D"
A/D Converter Resolution:	16 bit

PRESSURE SENSOR

Enclosure Material:	316 Stainless Steel
Cable Jacket Material:	Polyurethane
Operating Temp:	0 to +60 °C
Accuracy:	± 1.0 % full scale

Transmitter Subassembly: WTT40

Includes: 40 feet of Cable with Kellems Grip